

# FEDRIGONI

PAPER

## COROLLA LABEL

Laid paper certify FSC®, made with E.C.F. pulp. Wet-strength treatment suitable for labelling applications. Available in Premium White, Ivory and Beige colours.

DESCRIPTION

SIZE	GRAIN	SUBSTANCE
72X101	LG	80

RANGE

SUBSTANCE	V.S.A.	OPACITY	COBB 60	W.B.R.	DRY TENSILE STRENGTH	
ISO 536	ISO 534	ISO 2471	ISO 535	ISO 3781	ISO 1924	
g/m²	cm³/g	%	g/m²	%	kN/m	
80 ± 3%	1,22	87 ± 2	25 ± 4	≥8	long±10%	cross±10%

TECHNICAL  
FEATURES

ref. standard/instrument  
unit of measure

Brightness - ISO 2470 (R457)  
- 105% ± 2  
Relative Humidity 50% ± 5  
ref. TAPPI 502-98



ECOLOGICAL  
FEATURES

The product is completely biodegradable.  
Special runs available upon request.


NOTES

# COROLLA LABEL

Corolla Label is an uncoated laid paper which has been specially developed for the labels sector. For labelling, always observe the correct indications as regards grain direction. It must be parallel to the base of the bottle (see drawings).


## APPLICATIONS

Form of the label




wrap-around label

Rolling after wetting the back of the label.



correct grain direction



wrong grain direction

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography, screen printing and bronzing. The macro-porous surface requires the use of oxidative drying inks.

## PRINTING SUGGESTIONS

The varnishing coated with an offset machine is almost fully absorbed and therefore does not improve gloss or protection.

Good results with major processing operations such as: cutting, die-cutting and glueing.

## CONVERTING SUGGESTIONS