


## **SYMBOL CARD**

Environmentally-friendly E.C.F. boards, certify FSC\*. Double blade coated on one side with a Satin finish. Available in Premium White shade.

DESCRIPTION

SIZE	GRAIN	SUBSTANCE
72X102	LG	210 240 270 300 330 360





SUBSTANCE	THICKNESS	ROUGHNESS*	TABER STIF	TABER STIFFNESS 15°	
ISO 536	ISO 534	ISO 8791-2	ISO 2493	ISO 2493	
g/m²	μm	ml/min	mN	mN	
			long ± 15%	cross ± 15%	
				,	
210 ± 4%	250 ± 10	$350 \pm 50$	85	50	
240 ± 5%	285 ± 10	$350 \pm 50$	110	70	
270 ± 5%	325 ± 10	$350 \pm 50$	160	100	
300 ± 5%	360 ± 10	$350 \pm 50$	200	125	
330 ± 5%	400 ± 15	$350 \pm 50$	250	160	
360 ± 5%	437 ± 15	$350\pm50$	290	190	

## TECHNICAL FEATURES

ref. standard/instrument unit of measure

Brightness - ISO 2470 (R457) - 104%  $\pm$  2 Relative Humidity 50%  $\pm$  5 ref. TAPPI 502-98 \* Uncoated side











ECOLOGICAL FEATURES

The product is completely bio-degradable and recyclable. Special runs available upon request.

**NOTES** 

## SYMBOL CARD

Symbol Card is excellent for packaging, covers, postcards, brochures, promotional material, greeting cards and similar applications.

**APPLICATIONS** 

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen-printing. For offset printing, the characteristics of the coated side are comparable to our Symbol Freelife Satin, and the uncoated side is designed to provide good printability, also with solid colours.

PRINTING SUGGESTIONS

Good results can be expected with all the main converting process: cutting, die-cutting, scoring, glueing, varnishing and plastic lamination.

CONVERTING SUGGESTIONS

