


SYMBOL CARD

Environmentally-friendly E.C.F. boards, certify FSC[®]. Double blade coated on one side with a Satin finish. Available in Premium White shade.

DESCRIPTION

 SIZE
 GRAIN
 SUBSTANCE
 RANGE

 72X102
 LG
 210 240 270 300 330 360 400
 RANGE



SUBSTANCE	THICKNESS	ROUGHNESS*	TABER STIFFNESS 15° ISO 2493	
ISO 536	ISO 534	ISO 8791-2		
g/m²	μm	ml/min	mN	
			long ± 15%	cross±15%
210 ± 4%	250 ± 10	350 ± 50	85	50
240 ± 5%	285±10	350 ± 50	110	70
270 ± 5%	325 ± 10	350±50	160	100
300±5%	360±10	350 ± 50	200	125
330 ± 5%	400 ± 15	350 ± 50	250	160
360±5%	437 ± 15	350 ± 50	290	190
400 ± 5%	480±20	350 ± 50	365	230



The product is completely recyclable. Special runs available upon request.

TECHNICAL FEATURES

ref. standard/instrument unit of measure

Brightness - ISO 2470 (R457) - 104% ± 2 Relative Humidity 50% ± 5 ref. TAPPI 502-98 * Uncoated side

ECOLOGICAL FEATURES

NOTES

PRODUCT DATA SHEET SYM/462 Update 02/2024 Rev. n° 13

SYMBOL CARD

Symbol Card is excellent for covers, postcards, brochures, promotional material,	APPLICATIONS
greeting cards and similar applications.	

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen-printing. For offset printing, the characteristics of the coated side are comparable to our Symbol Freelife Satin, and the uncoated side is designed to provide good printability, also with solid colours. PRINTING SUGGESTIONS

Good results can be expected with all the main converting process: cutting, die-cutting, scoring, glueing, varnishing and plastic lamination.

CONVERTING SUGGESTIONS

