

## **TINTORETTO LABEL**

Uncoated felt-marked paper certify FSC®, made with E.C.F. (Elemental Chlorine Free) pulp. Wet-strength treatment suitable for labelling applications. Available in Gesso and Crema colours. It ensures high performances in terms of wet and dry high opacity.

DESCRIPTION

SIZE	GRAIN	SUBSTANCE
72X101	LG	95

RANGE

SUBSTANCE	BULK	OPACITY		COBB 60	W.B.R.	DRY TENSILE STRENGTH	
ISO 536	ISO 534	ISO 2471		ISO 535	ISO 3781	ISO 1924	
g/m²	cm³/g	%		g/m²	%	kN/m	
		DRY	WET			long±10%	trasv±10%
95 ± 3%	1,4	92±2	≥88	25 ± 4	≥9	6,4	3,8

## **TECHNICAL FEATURES**

ref. standard/instrument unit of measure

Brightness (col. Gesso) ISO 2470 (R457) - 100% ± 2

Relative Humidity 50% ± 5 ref. TAPPI 502-98

Roughness Bendtsen (ISO 8791-2) Top  $.750 \pm 100$  ml/min.
















Special runs available upon request.

**NOTES** 

## **TINTORETTO LABEL**

Tintoretto Label is an uncoated, felt-marked paper developed for wet glue labels. For labelling, always observe the correct indications as regards grain direction. It must be parallel to the base of the bottle (see drawings).

**APPLICATIONS** 



Suitable with the main printing systems: offset, blind embossing, hot foil stamping, thermography, screen printing and bronzing. Its macroporous surface requires the use of oxidative drying inks.

PRINTING SUGGESTIONS

The varnish printed with an offset machine is almost fully absorbed and therefore it doesn't improve gloss or protection. Good results with major processing operations such as: cutting, die-cutting and glueing.

CONVERTING SUGGESTIONS

