### FEDRIGONI SPECIAL PAPERS



# SYMBOL PACK PREMIUM WHITE

Creasing normally comes after different and expensive conversions like printing, hot foil embossing or blind embossing. In Fedrigoni we know how important this final step on the folding boxes manufacturing process is to get the best result and especially to avoid extra costs or material waste.	INTRODUCTION
The creasing process has dozens of possibilities for one single thickness, but only one guarantees the perfect result. Fedrigoni is the world leader in special papers, we are experts on paper manufacturing but not in creasing, for that reason we have worked together with CITO, the European leader of creasing tools for getting the perfect combination for our papers.	
Thanks to CITO's technology we have tested each one of our grammages with more than 100 different setups and have check all of them at a microscopical level looking for the perfect shape.	
The mentioned sizes are recommendations only. Other factors can influence the material and thus have an effect on the choice of the counterpart or the creasing rule.	IDEAL SCENARIO
We also would like to emphasize that the result was achieved with original CITO creasing matrix. Other creasing matrix can differ in the dimensions leading to different results. While the result for the milled steel counter plate shall remain the same.	

Machine: BOBST SP 104 ER Creasing Matrix: CITO ULTIMATE Milled channels at steel counter: conical 15-20°

TRIAL SCENARIO

PRODUCT DATA SHEET SYMBOL PACK/4B6 Update 10/2024 Rev. n° 00



#### **FEDRIGONI** SPECIAL PAPERS



# **SYMBOL PACK PREMIUM WHITE**

g/m²	Paper Thickness (um)		asing (mm)	Creasing Matrix (mm)	Scoring Rule (mm)		CREASING MATRIX PHENOLIC COUNTER	
		Height	Width	CITO ULTIMATE along and against the grain	Height	Width		
230	255	23.55	0.71 / 2 Pt.	0.3 × 1.0	23.65	0.71 / 2 Pt.	1.017 mm 153" 0.121 mm 161"	
250	280	23.50	0.71 / 2 Pt.	0.3×1.1	23.65	0.71 / 2 Pt.	1.030 mm 152" 0.125 mm 155"	
280	315	23.50	0.71 / 2 Pt.	0.3×1.1	23.65	0.71 / 2 Pt.	1.108 mm 0.167 mm 148° 135°	
310	345	23.45	0.71 / 2 Pt.	0.3 × 1.2	23.65	0.71 / 2 Pt.	1.253 mm 1.253 mm 152 <sup>-</sup> 150 <sup>-</sup>	
330	380	23.45	0.71 / 2 Pt.	0.4×1.3	23.60	0.71 / 2 Pt.	0.170 mm 140 <sup>-</sup> 143 <sup>-</sup>	
360	420	23.45	0.71 / 2 Pt.	0.4×1.3	23.60	0.71 / 2 Pt.	0.120 mm 147* 144*	
400	450	23.35	0.71 / 2 Pt.	0.5 × 1.4	23.60	0.71 / 2 Pt.	1.457 mm 0.184 mm 140*	







Ā





LEGENDA

GROOVE WIDTH

MATRIX/PHENOLIC COUNTER THICKNESS (MM)

CREASING RULE HEIGHT

CREASING RULE WIDTH

h

SCORING RULE HEIGHT


#### FEDRIGONI SPECIAL PAPERS





## SYMBOL PACK PREMIUM WHITE


g/m²	Paper Thickness (um)	Cre Rule	easing e (mm)	Channel (mm)	Scoring Rule (mm)		1
		Height	Width	along and against the grain	Height	Width	
230	255	23.85	0.52 / 1.5 Pt.	0.6/1.0	23.65	0.71 / 2 Pt.	ſ
250	280	23.80	0.71 / 2 Pt.	0.6/1.1	23.60	0.71 / 2 Pt.	
280	315	23.80	0.71 / 2 Pt.	0.6/1.2	23.60	0.71 / 2 Pt.	r
310	345	23.80	0.71 / 2 Pt.	0.6/1.3	23.60	0.71 / 2 Pt.	r
330	380	23.80	0.71 / 2 Pt.	0.6/1.3	23.60	0.71 / 2 Pt.	ſ
360	420	23.80	0.71 / 2 Pt.	0.6/1.4	23.60	0.71 / 2 Pt.	F
400	450	23.80	0.71 / 2 Pt.	0.6/1.4	23.60	0.71 / 2 Pt.	F































LEGENDA

CHANNEL DEPTH MILLED STEEL CREASING RULE HEIGHT

CREASING RULE WIDTH

h

SCORING RULE HEIGHT