

## SYMBOL CARD HIGH BULK

Board made with E.C.F. and BCTMP celluloses, FSC® certified. Double blade coated on one side with a Satin finishing and an high-bulk substrate. Available in Premium White shade.

DESCRIPTION

RANGE

SUBSTANCE

260 280 300



SUBSTANCE	THICKNESS	ROUGHNESS*	TABER STIFFNESS 15° ISO 2493	
ISO 536	ISO 534	ISO 8791-2		
			long ± 10%	trasv ± 10%
g/m²	μm	ml/min	mN	mN
260 ± 5%	370 ± 15	550 ± max 600	190	110
280 ± 5%	400 ± 15	550 ± max 600	230	130
300 ± 5%	425 ± 20	550 ± max 600	310	155

## TECHNICAL FEATURES

Ref. standard/instrument unit of measure

Brightness - ISO 2470 (R457) -  $102\% \pm 2$  (Coated side).

Brightness - ISO 2470 (R457) - 102% ± 2 (Uncoated side).

Relative Humidity  $55\% \pm 5$  ref. TAPPI 502-98

\* Uncoated side









ECOLOGICAL FEATURES

The product is completely recyclable. Special runs available upon request.

NOTES

## **SYMBOL CARD HIGH BULK**

Symbol Card High Bulk is excellent for sleeves, brochures, promotional material, greeting cards and similar applications.

**APPLICATIONS** 

Can be used without problems with the main printing systems: offset, blind embossing, hot foil stamping and screen-printing. For offset printing, the features of the coated side are comparable to Satin finishing and the uncoated side is designed to provide good printability also with solid colours.

PRINTING SUGGESTIONS

Good results can be expected with all the main converting process: cutting, die-cutting, scoring, glueing, varnishing and plastic lamination.

CONVERTING SUGGESTIONS

