

SYMBOL CARD

Environmentally-friendly E.C.F. boards, certify FSC®. Double blade coated on one side with a Satin finish. Available in Premium White shade.

DESCRIPTION

SIZE	GRAIN	SUBSTANCE
72X102	LG	210 240 270 300 330 360 380 400

RANGE



SUBSTANCE	THICKNESS	ROUGHNESS*	TABER STIFFNESS 15°	
ISO 536	ISO 534	ISO 8791-2	ISO 2493	
g/m²	µm	ml/min	mN	
			long ± 15%	cross ± 15%
210 ± 4%	250 ± 10	350 ± 50	85	50
240 ± 5%	285 ± 10	350 ± 50	110	70
270 ± 5%	325 ± 10	350 ± 50	160	100
300 ± 5%	360 ± 10	350 ± 50	200	125
330 ± 5%	400 ± 15	350 ± 50	250	160
360 ± 5%	437 ± 15	350 ± 50	290	190
380 ± 5%	450 ± 15	350 ± 50	310	200
400 ± 5%	480 ± 20	350 ± 50	365	230

TECHNICAL
FEATURES

ref. standard/instrument
unit of measure

Brightness - ISO 2470
(R457) - 104% ± 2
Relative Humidity 50% ± 5
ref. TAPPI 502-98
* Uncoated side



ECOLOGICAL
FEATURES

The product is completely bio-degradable and recyclable. Special runs available upon request. Symbol Card 400 gsm is is produced by special runs available upon request, and need a minimum lot of production.

NOTES

SYMBOL CARD

Symbol Card is excellent for packaging, covers, postcards, brochures, promotional material, greeting cards and similar applications.

APPLICATIONS

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen-printing. For offset printing, the characteristics of the coated side are comparable to our Symbol Freelifa Satin, and the uncoated side is designed to provide good printability, also with solid colours.

**PRINTING
SUGGESTIONS**

Good results can be expected with all the main converting process: cutting, die-cutting, scoring, glueing, varnishing and plastic lamination.

**CONVERTING
SUGGESTIONS**

