

FEDRIGONI

PAPER

SYMBOL PACK ECO 50

Environmentally-friendly recycled paper boards, made with 50% recycled material certify FSC® and 50% pure virgin fibers certify FSC®. Double blade coated on top surface with a Satin finishing. Available in Premium White shade.

DESCRIPTION

SIZE	GRAIN	SUBSTANCE
72X102	LG	310 330 360 400

RANGE



SUBSTANCE	THICKNESS	ROUGHNESS*	TABER STIFFNESS 15°			
			long ± 15%		trasv ± 15%	
ISO 536	ISO 534	ISO 8791-2	ISO 2493			
g/m ²	µm	ml/min	mN	mNm	mN	mNm
310 ± 5%	330 ± 10	300 ± 50	260	12,5	130	6,2
330 ± 5%	360 ± 10	300 ± 50	330	15	160	7,6
360 ± 5%	400 ± 10	300 ± 50	395	18	190	9
400 ± 5%	430 ± 15	300 ± 50	450	22	220	11

TECHNICAL FEATURES

ref. standard/instrument
unit of measure

Brightness - ISO 2470 (R457) -
103% ± 2 (Coated side).
CIE Whiteness - 138 ± 4 (Coated side).

Nuance L* 94% ± 1,0
a* 2,8% ± 0,8
b* - 11,5% ± 0,8

Brightness - ISO 2470 (R457) -
103% ± 2 (Uncoated side).
CIE Whiteness - 139,5 ± 4 (Uncoated side).

Relative Humidity 55% ± 5 ref.
TAPPI 502-98

* Uncoated side

ECOLOGICAL FEATURES



The product is completely recyclable. Given the considerable amount of recycled content within the substrate it's possible for there to be a slight variation in the shade, from one making to the next and spots in the base substrate. Special runs available upon request.

NOTES

SYMBOL PACK ECO 50

Symbol Pack ECO 50 is excellent for packaging, folding boxes, sleeves, brochures, promotional material, greeting cards and similar applications.

APPLICATIONS

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography and screen-printing. For offset printing, the features of the coated side are comparable to Satin finishing and the uncoated side is designed to provide good printability also with solid colours

PRINTING SUGGESTIONS

Good results can be expected with all the main converting process: cutting, die-cutting, scoring, glueing, varnishing and plastic lamination.

CONVERTING SUGGESTIONS

