

## **WOVE WASH-OFF WS**

Wet-strength and alkali-resistant uncoated smooth paper for labels, specially designed to improve the washability of returnable bottles, made from pure E.C.F. (Elemental Chlorine Free) cellulose pulp, FSC® certified. Available in Ivory shade.

DESCRIPTION

SIZE	GRAIN	SUBSTANCE
72X102	LG	80

SUBSTANCE	BULK	OPACITY		COBB 60	W.B.R.	DRY TENSILE STRENGTH	
ISO 536	ISO 534	ISO 2471		ISO 535	ISO 3781	ISO 1924	
g/m²	cm³/g	%		g/m²	%	kN/m	
		DRY	WET			long±10%	trasv±10%
80 ± 3%	1,2	91±2	≥84	21 ± 4	≥18	7	3,3

## TECHNICAL FEATURES

RANGE

ref. standard/instrument unit of measure

Brightness (col. Ivory) ISO 2470  $68\% \pm 2$ 

Relative Humidity  $50\% \pm 5$  ref. TAPPI 502-98

Roughness Bendtsen (ISO 8791-2) Top. 315 ± 50 ml/min.















SPECIFIC TREATMENTS

ECOLOGICAL FEATURES


Special runs available upon request.

NOTES

## **WOVE WASH-OFF WS**

Wove Wash-off WS is an uncoated smooth paper developed for wet glue labels. For labelling, always observe the correct indications as regards grain direction. It must be parallel to the base of the bottle (see drawings).

APPLICATIONS



Suitable with the main printing systems: offset, blind embossing, hot foil stamping, thermography, screen printing and flexography. The macroporous surface requires the use of oxidative drying inks.

PRINTING SUGGESTIONS

The varnish coated with an offset machine is almost fully absorbed and therefore does not improve gloss or protection. Good results with major processing operations such as: cutting, die-cutting and glueing.

CONVERTING SUGGESTIONS

